

1.

2.

3.

		Qnet. ar	(Vdaf)	St. d	Na <sub>2</sub> O	M	DT
50mm		4800kcal kg	18% 38%	2.5 %	2.0 %	8%	1350
		4600kcal kg	15% 40%	4.0 %	2.0 %	---	---

1.

5

3000

2.

2024 2 1 10

< 1 10

1 2 15 8 3000

2 15 8 5000

20 /

8000

0.02 / .

3.

13 %

4.

10

2304343109122102320

5.

## 2024 2

	Qnet. ar 4800 St. d 2.5% 18% Vdaf 38% Na <sub>2</sub> O 2.0% 0. xxx / .	Qnet. ar <4800 Kcal / Qnet. ar 100 0.005 / . 100 38%<Vdaf 40% Vdaf 1 0.002 / Vdaf 40% . 1 0.005 / . 8000 < 12000 8000 0.02 / . >12000 12000 0.03 / .	1. 2.5%<St. d 3.0% St. d 0.1 1 2. 3.0%<St. d 3.5% St. d 0.1 2 3. St. d>3.5% St. d 0.1 5	90-110% 80% <90% -0.002 / 70% <80% 60% -0.004 / . <70% -0.006 / 50% <60% -0.008 / 40% <50% -0.010 / . <40% -0.020 / .				
		Qnet. ar 4600Kcal / St. d 4.0% 15% Vdaf 40% Na <sub>2</sub> O 2.0%	Qnet. ar <4600 St. d 4% Vdaf <15% Vdaf 40% 2.0% Vdaf <15% 20 / Vdaf <18% 20 /					
			( / . )	(%)	%		%	
				18% Vdaf 38%	2.5%	4800	2.0%	

1. 3000 3
- 2.
3. Qnet. ar 4800kcal St. d 2.5% 18% Vdaf 38% 2.0%
- 4.
- 5.
6. 0 1 10
- .

0 0- 0 0 0- 0

[cnf.dmtbj.cg@163.com](mailto:cnf.dmtbj.cg@163.com)

